

## OFFICIAL LISTING

NSF International Certifies that the products appearing on this Listing conform to the requirements of NSF/ANSI Standard 169 - Special Purpose Food Equipment and Devices

This is the Official Listing recorded on September 9, 2013.

CEME S.p.A. Via del Lavoro 2 20061 Carugate (MI) Italy 39 03 833 77405



Facility: Guangdong Province, China

Fitting <sup>[1]</sup> Pipetta Valve (Valvola) <sup>[1]</sup> S1 S11 <sup>[3]</sup> Water Oscillating EAP4 <sup>[Pb]</sup> EFP4 <sup>[Pb]</sup> EFP4 <sup>[Pb]</sup> EP45 <sup>[Pb]</sup> EP4RGW <sup>[Pb]</sup> EP5R <sup>[Pb]</sup> EP8RGW <sup>[Pb]</sup> EP8RGW <sup>[2]</sup> EX5GW <sup>[3]</sup>	$\begin{bmatrix} 2 \\ S2 \end{bmatrix}$ $\begin{bmatrix} 4 \\ S2 \end{bmatrix}$ $\begin{bmatrix} 4 \\ S2 \end{bmatrix}$ $\begin{bmatrix} 4 \\ S2 \end{bmatrix}$ $\begin{bmatrix} 2 \\ S2 \end{bmatrix}$ $\begin{bmatrix} 2$	[1] [2] ge	90° <sup>[2]</sup> S3 EAP7 <sup>[Pb]</sup> EFP7 <sup>[Pb]</sup> EK2GW <sup>[Pb]</sup> EP4FMGW <sup>[Pb]</sup> EP5FM <sup>[Pb]</sup> EP77 <sup>[Pb]</sup> EP8LT <sup>[Pb]</sup> EX4FM <sup>[3]</sup> EX5 <sup>[3]</sup>	S3BP	Raccordo Bar <sup>[</sup> S3HP EAX4 EFX4 EN4 <sup>[Pb]</sup> EP4Gw <sup>[Pb]</sup> EP5FMGw <sup>[Pb]</sup> EP77Gw <sup>[Pb]</sup> EP8LTGw <sup>[Pb]</sup> EX4FMGw <sup>[3]</sup> EX5FM <sup>[3]</sup>	S3HP/R	S4 EAX5 EFX5 EP4 <sup>[Pb]</sup> EP4R <sup>[Pb]</sup> EP5GW <sup>[Pb]</sup> EP7GW <sup>[Pb]</sup> EP8R <sup>[Pb]</sup> EX4GW <sup>[3]</sup>	
Water Oscillating	Pump - HF <sup>[1]</sup>	[2]						
HF HF/S	HF2	HF2/S						
Water Oscillating NME1 <sup>[2]</sup> NME3S <sup>[2]</sup> NMEHP2 <sup>[2]</sup> NMEHP4/S <sup>[2]</sup>	Pump - NME R NME1C <sup>[2]</sup> NME4 <sup>[2]</sup> NMEHP2/S <sup>[2]</sup>		NME1S <sup>[2]</sup> NMECC NMEHP3 <sup>[2]</sup>		NME2 <sup>[2]</sup> NMEHP1 <sup>[2]</sup> NMEHP3/S <sup>[2]</sup>		NME3 <sup>[2]</sup> NMEHP1/S <sup>[2]</sup> NMEHP4 <sup>[2]</sup>	

NMEHP4/S<sup>L</sup>

[1] Models produced at this facility will bear a 'c' on the label.

- [2] Not acceptable for use in contact with alcoholic beverages.
- [3] Only acceptable for use in contact with coffee, tea, and potable water.
- [4] Only acceptable for use in contact with non-carbonated, potable water with a maximum contact temperature of 82°C.
- [Pb] Product also evaluated and determined to possess weighted average lead content of <=0.25% and is in compliance with California's Health & Safety Code Section 116875 (commonly known as AB1953) and Vermont Act 193.

## Facility: Trivolzio (PV), Italy

Fitting

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International.

Pipetta	Raccor	dino 90° <sup>[1]</sup>		Raccordo Bar <sup>[2]</sup>		
Valve (Valvola) <sup>[1]</sup> S1 <sup>[2]</sup> S11 <sup>[2]</sup>	S2 S22	<sup>3]</sup> s3	S3BP	S3HP	S3HP/R	S4
Water Oscillating EAP4 <sup>[Pb]</sup> EFP4 <sup>[Pb]</sup> EP4 <sup>[Pb]</sup> EP4 <sup>[Pb]</sup> EP5GW <sup>[Pb]</sup> EP5GW <sup>[Pb]</sup> EP8R <sup>[Pb]</sup> EX4GW <sup>[2]</sup>	EAP5 <sup>[PD]</sup> EFP5 <sup>[Pb]</sup> EF45 <sup>[Pb]</sup> EP45 <sup>[Pb]</sup> EP4RGW <sup>[Pb]</sup> EP8 <sup>[Pb]</sup> EP8RGW <sup>[Pb]</sup> EX4R <sup>[2]</sup> EX5GW <sup>[2]</sup>	EAP7 <sup>[Pb]</sup> EFP7 <sup>[Pb]</sup> EK2GW <sup>[Pb]</sup> EP4FM <sup>[Pb]</sup> EP5 <sup>[Pb]</sup> EP7 <sup>[Pb]</sup> EP8GW <sup>[Pb]</sup> EX4 <sup>[2]</sup> EX4RGW <sup>[2]</sup>		EAX4 EFX4 EN4 <sup>[Pb]</sup> EP4FMGW <sup>[Pb]</sup> EP5FM <sup>[Pb]</sup> EP77 <sup>[Pb]</sup> EP8LT <sup>[Pb]</sup> EX4FM <sup>[2]</sup> EX5 <sup>[2]</sup>		EAX5 EFX5 EN4FM EP4GW <sup>[Pb]</sup> EP5FMGW <sup>[Pb]</sup> EP77GW <sup>[Pb]</sup> EP8LTGW <sup>[Pb]</sup> EX4FMGW <sup>[2]</sup> EX5FM <sup>[2]</sup>
Water Oscillating	Pump - HF					
HF HF/S	HF2 HF2/	S				
Water Oscillating NME1 <sup>[1]</sup> NME3S <sup>[1]</sup> NMEHP2 <sup>[1]</sup> NMEHP4/S <sup>[1]</sup>	Pump - NME Range NME1C <sup>[1]</sup> NME4 <sup>[1]</sup> NMEHP2/S <sup>[1]</sup>	NME1S <sup>[1]</sup> NMECC NMEHP3 <sup>[1]</sup>		NME2 <sup>[1]</sup> NMEHP1 <sup>[1]</sup> NMEHP3/S <sup>[1]</sup>		NME3 <sup>[1]</sup> NMEHP1/S <sup>[1]</sup> NMEHP4 <sup>[1]</sup>

[1] Not acceptable for use in contact with alcoholic beverages.

- [2] Only acceptable for use in contact with coffee, tea, and potable water.
- [3] Only acceptable for use in contact with non-carbonated, potable water with a maximum contact temperature of 82°C.
- [Pb] Product also evaluated and determined to possess weighted average lead content of <=0.25% and is in compliance with California's Health & Safety Code Section 116875 (commonly known as AB1953) and Vermont Act 193.

Note: Additions shall not be made to this document without prior evaluation and acceptance by NSF International. 2 of 2