

## IKV-TRIBOGEAR 150

### ► DESCRIPTION

**IKV-TRIBOGEAR 150** is a premium industrial gear oil made from solvent refined high quality paraffinic mineral oils and an unleaded load carrying additive that delivers a high level of micropitting resistance in addition to high EP protection and thermal stability.

**IKV-TRIBOGEAR 150** offers an outstanding combination of characteristics that can facilitate enhanced performance in the applications in which they are used. Its excellent performances help to protect components and equipment, to extend their life and to reduce maintenance costs.

These properties include:

#### **-Outstanding high temperature performance**

Excellent resistance to oxidative breakdown even at high temperature allows to longer fluid life and helps to keep systems free of sludge and varnish.

#### **-Excellent lubrication**

The natural ability of the base oils to provide superior lubrication under a wide range of applications. Their low coefficient of friction reduces operating temperatures and power consumption.

#### **-Outstanding anti-wear and extreme pressure performance**

Helps prevent micropitting, seizure, scuffing and spalling under shock loading conditions, reduces gear and bearing wear and improves load bearing capability. Protects equipment operating at high production rates for extended periods in demanding conditions. Long reliable component life, resulting in greater plant utilization.

#### **-Good anticorrosion protection**

Provides an effective protection from moisture damage, prevents the formation of emulsions that cause rust and protects bronze and copper components.

#### **-Effective water separation**

Prevents emulsion formation and eliminates corrosive damage.

#### **-high resistance to foaming and air entrapment**

Avoids gear damage caused by insufficient lubricant film due to aeration and prevents reservoir overflow. Reduces also the possibility of cavitation damage to oil circulating pumps where installed.

#### **-Chemical compatibility**

Compatible with a wide range of elastomer materials but also plastics, coatings, paints used in equipment already lubricated with mineral or PAO oils.

## IKV-TRIBOGEAR 150

**IKV-TRIBOGEAR 150** meets or exceeds the performance requirements of:

- SIEMENS MD APPROVAL FOR FLENDER GEARBOXES-REVISION 14
- DIN 51517 PART 3
- U.S. Steel 224
- AGMA 9005-E02
- ISO 12925-1 CKC/CKD
- David Brown S1.53.101
- GM LS 2 EP Gear Oil
- Fives Cincinnati Machine Gear

**IKV-TRIBOGEAR 150** is classified CKD 150 according to ISO DP 6743/6 standard, CC 150 according to the NF E 60-200 standard and cat CLP according to DIN 51517 part 3.

### ► TYPICAL APPLICATIONS

**IKV-TRIBOGEAR 150** is appropriated for use in all types of enclosed industrial gear drives where an extreme pressure and long life oil is required. It is suitable for the lubrication of heavily loaded gears including Spur, Internal, Helical, Planetary, Bevel, Spiral-Bevel, Rack & Pinion, and Worm gears and provides protection in applications where shock loading occurs.

**IKV-TRIBOGEAR 150** can also be used in circulating systems in heavies industries such as ports installations, cement works and mechanical industries in general.

**IKV-TRIBOGEAR 150** is also effective wire-rope lubricants.



The values quoted above are typical of normal production. They do not constitute a specification. The information set forth herein is furnished free of charge and based on technical data that IKV TRIBOLOGIE believes to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. Because conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents.

## IKV-TRIBOGEAR 150

### ► PROPERTIES

CHARACTERISTICS	VALUES	UNITS	TESTS
Oil nature	Mineral		
Kinematic viscosity at 40°C	150	cSt	ASTM D-445
Flash point	> 270	°C	ASTM D-92
Pour point	-20	°C	ASTM D-97
Density	0.895	g / cm <sup>3</sup>	ASTM D-1298
Copper Corrosion test (3 hrs @ 100°C)	1b		ASTM D-130
FZG Scuffing (A/8,3/90)	> 12	stage	DIN 51354
Useful temperature range	-15 / 110	°C	
<b>4 balls test</b>			
4 balls test - Scar diameter (1h-40kg @75°C)	< 0.5	mm	ASTM D-4172

4/2022