

Safety Data Sheet dated 1/12/2022, version 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier Mixture identification: Trade name: **OLIO SPRAY PER CARTELLE** Trade code: 11.026/100 - 11.026 UFI UP00-00JD-K00H-Y323 1.2. Relevant identified uses of the substance or mixture and uses advised against Recommended use: PRODUCTS FOR AIR CONDITIONING SYSTEMS Uses advised against: do not use on humans and animals 1.3. Details of the supplier of the safety data sheet Company: ELKE S.r.I. Via XXV Aprile 202 10042 Nichelino (To) Italia. Tel. n. +39 011 9622412 Competent person responsible for the safety data sheet: Domenico Amosso info@elke-ac.com 1.4. Emergency telephone number Centro Antiveleni di Milano 02 66101029 (CAV Ospedale Niguarda Ca' Granda -Milano) Centro Antiveleni di Pavia 0382 24444 (CAV IRCCS Fondazione Maugeri - Pavia) Centro Antiveleni di Bergamo 800 883300 (CAV Ospedali Riuniti - Bergamo) Centro Antiveleni di Firenze 055 7947819 (CAV Ospedale Caregoi - Firenze) Centro Antiveleni di Roma 06 3054343 (CAV Policlinico Gemelli - Roma) Centro Antiveleni di Roma 06 49978000 (CAV Policlinico Umberto I - Roma) Centro Antiveleni di Napoli 081 7472870 (CAV Ospedale Cardarelli - Napoli) Centro Antiveleni di Verona 800 011858 (CAV Ospedale AOUI- Verona) Centro Antiveleni di Foggia 800 183459 (CAV Policlinico Riuniti-Foggia) Centro Antiveleni di Roma 06 68593726(CAV Ospedale Bambino Gesù-Roma)

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture
- EC regulation criteria 1272/2008 (CLP):

Danger, Aerosols 1, Extremely flammable aerosol. Pressurized container: may burst if heated.

Adverse physicochemical, human health and environmental effects:

No other hazards 2.2. Label elements Hazard pictograms:



smoking.

Danger Hazard statements: H222, H229 Extremely flammable aerosol. Pressurized container: may burst if heated. Precautionary statements: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

11.026/100 - 11.026 Page n. 1 of 10



P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. Special provisions according to Annex XVII of REACH and subsequent amendments:

None 2.3. Other hazards

No PBT, vPvB or endocrine disruptor substances present in concentration >= 0.1% Other Hazards:

No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Numb	er	Classification
>= 40% - < 50%	propane	Index number: CAS: EC: REACH No.:	601-003-00-5 74-98-6 200-827-9 01- 2119486944- 21-0046	 2.2/1 Flam. Gas 1 H220 2.5 Press. Gas H280
>= 25% - < 30%	White mineral oil (petroleum)	CAS: EC:	8042-47-5 232-455-8	🕸 3.10/1 Asp. Tox. 1 H304
>= 15% - < 20%	Hydrocarbons, C4; Petroleum gas	Index number: CAS: EC: REACH No.:	649-113-00-2 87741-01-3 289-339-5 01- 2119480480- 41-xxxx	 2.5 Press. Gas H280 2.2/1 Flam. Gas 1 H220 DECLK (CLP)*
>= 5% - < 7%	Hydrocarbons, C9- C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	CAS: EC: REACH No.:	64742-48-9 919-857-5 01- 2119463258- 33-xxxx	 3.10/1 Asp. Tox. 1 H304 3.8/3 STOT SE 3 H336 2.6/3 Flam. Liq. 3 H226

*DECLK (CLP): This substance is classified in accordance with Note K, Annex VI of EC Regulation CE 1272/2008. The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w 1,3- butadiene (Einecs No 203-450-8), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P210-P403 shall apply.

SECTION 4: First aid measures

4.1. Description of first aid measures
In case of skin contact: Wash with plenty of water and soap.
In case of eyes contact:
In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

11.026/100 - 11.026 Page n. 2 of 10



In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

- 4.2. Most important symptoms and effects, both acute and delayed
- For symptoms and effects due to the contained substances see chapter 11
- 4.3. Indication of any immediate medical attention and special treatment needed Treatment:

Follow the doctor's instructions.

SECTION 5: Firefighting measures

- 5.1. Extinguishing media
 - Suitable extinguishing media:
 - CO2 or Dry chemical fire extinguisher.

Extinguishing media which must not be used for safety reasons: Water.

- 5.2. Special hazards arising from the substance or mixture Burning produces heavy smoke. Do not inhale explosion and combustion gases.
- 5.3. Advice for firefighters

Normal elements for fire fighting, such as a self-contained compressed air open-circuit respirator (EN 137), fire-retardant suit (EN469), flame-retardant gloves (EN 659) and fire boots (HO A29 or A30).

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Keep containers cool with water spray.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

 6.1. Personal precautions, protective equipment and emergency procedures Wear personal protection equipment. Remove all sources of ignition. Remove persons to safety.

See protective measures under point 7 and 8.

- 6.2. Environmental precautions Suitable material for taking up: absorbing material, organic, sand Retain contaminated washing water and dispose it.
- 6.3. Methods and material for containment and cleaning up For cleaning up: Wash with plenty of water.
- 6.4. Reference to other sections
 - See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists. Do not use on extensive surface areas in premises where there are occupants. Don't use empty container before they have been cleaned. Before making transfer operations, assure that there aren't any incompatible material residuals in the containers. Advice on general occupational hygiene: Do not eat, drink or smoke when using this product. Contamined clothing should be changed before entering eating areas.



Wash hands after use

7.2. Conditions for safe storage, including any incompatibilities

store in a cool, well ventilated place, away from heat, flames, sparks or other sources of ignition

keep only in the original container away from sunlight neighborhoods

avoid contact with skin and eyes, inhalation of vapours/mists/dusts.

do not use empty containers before they are cleaned.

contaminated clothing must be replaced before entering the dining areas.

- at work do not eat or drink.
- do not smoke

avoid the accumulation of electrostatic charges.

Store at below 50 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

- Cool and adequately ventilated.
- 7.3. Specific end use(s)

olio

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

propane - CAS: 74-98-6 ACGIH White mineral oil (petroleum) - CAS: 8042-47-5 TLV-ACGIH - STEL(): 10 mg/m3 TLV-ACGIH - TWA(8h): 5 mg/m3 **DNEL Exposure Limit Values** White mineral oil (petroleum) - CAS: 8042-47-5 Worker Professional: 220 mg/kg/8h - Exposure: Human Dermal - Frequency: Long Term. systemic effects Worker Professional: 160 mg/m3/8h - Exposure: Human Inhalation - Frequency: Long Term. systemic effects Consumer: 92 mg/kg/8h - Exposure: Human Dermal - Frequency: Long Term, systemic effects Consumer: 35 mg/m3/8h - Exposure: Human Inhalation - Frequency: Long Term, systemic effects Consumer: 40 mg/kg/d - Exposure: Human Oral - Frequency: Long Term, systemic effects **PNEC Exposure Limit Values** N.A. 8.2. Exposure controls Eye protection: Eye glasses with side protection. EN 166 Protection for skin: No special precaution must be adopted for normal use. Protection for hands: Protect hands with category II work gloves (ref. Directive 89/686 / EEC and standard EN 374). Use PVC or nitrile rubber gloves.

Respiratory protection:



if the TLV thresholds are exceeded, use a mask with filter type A (against vapors of organic compounds) in accordance with EN 141.

Thermal Hazards:

Do not expose to temperatures exceeding 50° c.

Environmental exposure controls:

emissions from production processes, including those from ventilation equipment should be inspected for the purposes of enforcement of environmental protection

do not dispose of the product in the environment

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties			
Properties	Value	Method:	Notes:
Physical state:	Liquid		
Colour:	Colourless		
Odour:	characteristic		
Melting point/freezing point:	Not Relevant		
Boiling point or initial boiling point and boiling range:	Not Relevant		
Flammability:	Flammable		
Lower and upper explosion limit:	Not Relevant		
Flash point:	< 0 ° C		
Auto-ignition temperature:	400°C (gas)		
Decomposition temperature:	Not Relevant		
pH:	Not Relevant		
Kinematic viscosity:	> 20,5 mm2/sec (40 °C)		
Solubility in water:	undissolvable		
Solubility in oil:	complete		
Partition coefficient n- octanol/water (log value):	Not Relevant		
Vapour pressure:	5 bar +/- 1		
Density and/or relative density:	0.610 kg/l +/- 0.05		
Relative vapour density:	>2		
	Particle cha	racteristics:	
Particle size:	N.A.		

9.2. Other information

Properties	Value	Method:	Notes:
Explosive properties:	section 10.3		

SECTION 10: Stability and reactivity

10.1. Reactivity

avoid contact with strong acids and bases and oxidizing agents.

11.026/100 - 11.026 Page n. 5 of 10



- 10.2. Chemical stability Stable under normal conditions
- 10.3. Possibility of hazardous reactions may form explosive vapor / air mixtures in places not well ventilated
 10.4. Conditions to avoid avoid the accumulation of electrostatic charges.
 - keep away from heat, sources of ignition
- 10.5. Incompatible materials oxidizing agents
- 10.6. Hazardous decomposition products the product is flammable, following combustion can lead to the formation of dangerous decomposition products by thermal decomposition can rid COx

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 Toxicological information of the product: **OLIO SPRAY PER CARTELLE** a) acute toxicity Not classified Based on available data, the classification criteria are not met b) skin corrosion/irritation Not classified Based on available data, the classification criteria are not met c) serious eye damage/irritation Not classified Based on available data, the classification criteria are not met d) respiratory or skin sensitisation Not classified Based on available data, the classification criteria are not met e) germ cell mutagenicity Not classified Based on available data, the classification criteria are not met f) carcinogenicity Not classified Based on available data, the classification criteria are not met a) reproductive toxicity Not classified Based on available data, the classification criteria are not met h) STOT-single exposure Not classified Based on available data, the classification criteria are not met i) STOT-repeated exposure Not classified Based on available data, the classification criteria are not met j) aspiration hazard Not classified Based on available data, the classification criteria are not met Toxicological information of the main substances found in the product: White mineral oil (petroleum) - CAS: 8042-47-5 a) acute toxicity: Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg Test: LC50 - Route: Inhalation - Species: Rat > 5000 mg/m3 - Duration: 4h



11.2. Information on other hazards
 Endocrine disrupting properties:
 No endocrine disruptor substances present in concentration >= 0.1%

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment. OLIO SPRAY PER CARTELLE

Not classified for environmental hazards

Based on available data, the classification criteria are not met

- White mineral oil (petroleum) CAS: 8042-47-5
 - a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Algae > 100 mg/l - Duration h: 48

Endpoint: EC50 - Species: Daphnia > 100 mg/l - Duration h: 48

Endpoint: LC50 - Species: Fish > 10000 mg/l - Duration h: 96

b) Aquatic chronic toxicity:

Endpoint: NOEL - Species: Fish > 1000 mg/l - Notes: 14/21/d

12.2. Persistence and degradability

None

White mineral oil (petroleum) - CAS: 8042-47-5

- Biodegradability: Not persistent and Biodegradable
- 12.3. Bioaccumulative potential N.A.
- 12.4. Mobility in soil
 - N.A.
- 12.5. Results of PBT and vPvB assessment vPvB Substances: None - PBT Substances: None
- 12.6. Endocrine disrupting properties

No endocrine disruptor substances present in concentration >= 0.1%

12.7. Other adverse effects None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force. Additional disposal information:

contaminated packaging should be sent for recovery or disposal in compliance with national regulations on waste management

reuse if possible. Product residues are to be considered hazardous waste. disposal must be entrusted to authorised waste management, in compliance with national and, where appropriate, local.

SECTION 14: Transport information

14.1. UN number or ID number	
ADR-UN number:	1950
IATA-Un number:	1950
IMDG-Un number:	1950
14.2. UN proper shipping name	
ADR-Shipping Name:	FLAMMABLE AEROSOLS
IATA-Technical name:	FLAMMABLE AEROSOLS
IMDG-Technical name:	FLAMMABLE AEROSOLS
1/1.3 Transport bazard class(es)	

14.3. Transport hazard class(es)

11.026/100 - 11.026

Page n. 7 of 10



ADR-Class:	2.5°F CAP. 2.2.2.1.6 UN1950
IATA-Class:	2.1
IMDG-Class:	2 Aerosols UN 1950
14.4. Packing group	
ADR-Packing Group:	N.A.
IATA-Packing group:	N.A.
IMDG-Packing group:	N.A.
14.5. Environmental hazards	
Marine pollutant:	No
14.6. Special precautions for user	
ADR-Transport category (Tur	nnel restriction code): D
IMDG-Technical name:	FLAMMABLE AEROSOLS
14.7. Maritime transport in bulk acc	ording to IMO instruments
N.A.	

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 98/24/EC (Risks related to chemical agents at work) Dir. 2000/39/EC (Occupational exposure limit values) Regulation (EC) n. 1907/2006 (REACH) Regulation (EC) n. 1272/2008 (CLP) Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013 Regulation (EU) n. 2020/878 Regulation (EU) n. 286/2011 (ATP 2 CLP) Regulation (EU) n. 618/2012 (ATP 3 CLP) Regulation (EU) n. 487/2013 (ATP 4 CLP) Regulation (EU) n. 944/2013 (ATP 5 CLP) Regulation (EU) n. 605/2014 (ATP 6 CLP) Regulation (EU) n. 2015/1221 (ATP 7 CLP) Regulation (EU) n. 2016/918 (ATP 8 CLP) Regulation (EU) n. 2016/1179 (ATP 9 CLP) Regulation (EU) n. 2017/776 (ATP 10 CLP) Regulation (EU) n. 2018/669 (ATP 11 CLP) Regulation (EU) n. 2018/1480 (ATP 13 CLP) Regulation (EU) n. 2019/521 (ATP 12 CLP) Regulation (EU) n. 2020/217 (ATP 14 CLP) Regulation (EU) n. 2020/1182 (ATP 15 CLP) Regulation (EU) n. 2021/643 (ATP 16 CLP) Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications: None Where applicable, refer to the following regulatory provisions : Directive 2012/18/EU (Seveso III) Regulation (EC) nr 648/2004 (detergents). Dir. 2004/42/EC (VOC directive) Provisions related to directive EU 2012/18 (Seveso III): Seveso III category according to Annex 1, part 1 Product belongs to category: P3a 15.2. Chemical safety assessment No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

11.026/100 - 11.026 Page n. 8 of 10



Text of phrases referred to under heading 3: H220 Extremely flammable gas. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H336 May cause drowsiness or dizziness. H226 Flammable liquid and vapour.

Hazard class and hazard category	Code	Description
Flam. Gas 1	2.2/1	Flammable gas, Category 1
Aerosols 1	2.3/1	Aerosol, Category 1
Press. Gas	2.5	Gases under pressure
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
STOT SE 3	3.8/3	Specific target organ toxicity - single exposure,
		Category 3

Paragraphs modified from the previous revision:

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Classification according to Regulation (EC) Nr. 1272/2008	Classification procedure
Aerosols 1, H222, H229	On basis of test data

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality. It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
ATE:	Acute Toxicity Estimate
ATEmix:	Acute toxicity Estimate (Mixtures)
CAS:	Chemical Abstracts Service (division of the American Chemical
	Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of
	Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport

11.026/100 - 11.026 Page n. 9 of 10



	Association" (IATA). International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.