

NETTOYANT POUR MOUSSE POLYURETHANE

FUNCTIONALITY

Solvent for cleaning traces of unhardened polyurethane foam and application aerosols.

Degreasing of metals.

- Cleaning of unhardened polyurethane foam (GEBSOMOUSSE, etc.) in the valve and the riser of aerosols and other application systems. Dissolves the foam instantly as long as no surface skin has formed (i.e. up to approximately 15 minutes after application, depending on humidity and temperature).
- Degreasing of metal parts before painting or gluing.
- Easy removal of unhardened traces, adhesives and sealants (epoxy, cyanoacrylate, silicones, etc.).
- Practical aerosol format:
 - the capillary tube enables injection in the required place.
 - minimum solvent consumption.
 - no risk of overturning.

Technical characteristics

Active ingredient	Ethyl acetate base
Propellant	Butane

Use

Directions for use

- Between each use of the polyurethane foam aerosol, spray the product into the valve using the capillary tube provided for this purpose and catch the liquid (on a cloth for example). Wear gloves.
- For degreasing, spray onto the parts and wipe with a clean, dry cloth as quickly as possible.

Storage

Store between +5 °C and +30 °C.

At 20 °C, the shelf life of the product in its original, sealed packaging is 18 months.

The Safety Data Sheet is available online at www.quickfds.com. The information provided in this data sheet is given in good faith and is the result of measurements done in our laboratory. Given the number of materials, the quality differences and the diversity of working methods, we recommend that users carry out preliminary testing under actual conditions of use.

This document may be modified without warning in line with changes to the products or according to our knowledge. We therefore recommend that you check that you have the latest version before using the product.