



ETK Acid Test Kit

ETK (P/N 475360)

SDS Revision Date (mm/dd/yyyy): 09/11/2019

Page 1 of 11

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label

: **ETK Acid Test Kit**

Other means of identification : ETK (P/N 475360)

Recommended use of the chemical and restrictions on use

: Oil refrigeration test kit
Restriction on use: None known

Chemical family

: Mixture.

Name, address, and telephone number
of the supplier:

Parker Hannifin Corporation - Sporlan Division

206 Lange Drive
Washington, MO, U.S.A.
63090

Supplier's Telephone # : (636) 239-1111

24 Hr. Emergency Tel # : Chemtrec 1-800-424-9300 (Within Continental U.S.); Chemtrec 703-527-3887
(Outside U.S.).

Name, address, and telephone number of
the manufacturer:

Refer to supplier

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Clear, red liquid. Solvent odor.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification :

Flammable liquids - Category 2

Serious eye damage/eye irritation - Category 2A

Skin Irritation - Category 2

Reproductive toxicity - Category 2

Specific target organ toxicity, single exposure - Category 3 (narcotic effects)

Specific Target Organ Toxicity, Repeated Exposure - Category 2

Aspiration Toxicity - Category 1

Label elements

Hazard pictogram(s)



Signal Word

DANGER!



ETK Acid Test Kit

ETK (P/N 475360)

SDS Revision Date (mm/dd/yyyy): 09/11/2019

Page 2 of 11

SAFETY DATA SHEET

Hazard statement(s)

Highly flammable liquid and vapor.
Causes skin irritation.
Causes serious eye irritation.
Suspected of damaging fertility or the unborn child.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.

Precautionary statement(s)

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking.
Keep container tightly closed.
Ground/Bond container and receiving equipment.
Use explosion-proof electrical and ventilating equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Wash thoroughly after handling.
Avoid breathing mist, vapors or spray.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/clothing and eye/face protection.

IF exposed or concerned: Get medical attention/advice.
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation occurs: get medical advice/attention.
Take off contaminated clothing and wash before re-use.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
If eye irritation persists: get medical advice/attention.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER or doctor/physician if you feel unwell.
If swallowed: Immediately call a poison center/doctor.
Do NOT induce vomiting.
In case of fire, use water fog, dry chemical, CO₂ or 'alcohol' foam.

Store in a well-ventilated place. Keep cool.
Keep container tightly closed.
Store locked up.

Dispose of contents/container in accordance with local regulation.

Other hazards

Other hazards which do not result in classification:
Ingestion can cause gastrointestinal irritation, nausea, and diarrhea.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

| <u>Chemical name</u> | <u>Common name and synonyms</u> | <u>CAS #</u> | <u>Concentration (% by weight)</u> |
|----------------------|-------------------------------------|--------------|------------------------------------|
| Toluene | Methylbenzene | 108-88-3 | 30.0 - 60.0 |
| Ethyl alcohol | Ethyl alcohol Ethyl hydrate | 64-17-5 | 30.0 - 60.0 |
| potassium hydroxide | Caustic potash Potassium hydrate | 1310-58-3 | 0.1 - 1.0 |



ETK Acid Test Kit

ETK (P/N 475360)

SDS Revision Date (mm/dd/yyyy): 09/11/2019

Page 3 of 11

SAFETY DATA SHEET

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

- Ingestion* : Seek immediate medical attention/advice. Do not induce vomiting. Never give anything by mouth to an unconscious person.
- Inhalation* : Immediately remove person to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Seek immediate medical attention/advice.
- Skin contact* : Remove/Take off immediately all contaminated clothing. Wash off immediately with plenty of water for at least 15 minutes. If irritation persists, seek prompt medical attention.
- Eye contact* : Immediately flush eyes with running water for at least 20 minutes. Seek immediate medical attention/advice.

Most important symptoms and effects, both acute and delayed

- : May cause drowsiness or dizziness. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects. May cause skin irritation. Symptoms may include redness, itching and swelling. May cause severe eye irritation. Symptoms will include pain, redness and tearing. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause damage to the central nervous system through prolonged or repeated exposure if inhaled. Suspected of damaging the unborn child.

Indication of any immediate medical attention and special treatment needed

- : Treat symptomatically. Aspiration hazard This product is a CNS depressant.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

- : Dry chemical, foam, carbon dioxide and water fog. Do not use water jet, as this may spread burning material.

Unsuitable extinguishing media

- : Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture / Conditions of flammability

- : Highly flammable liquid and vapor. Vapour may cause flash fire! Vapours are heavier than air and may spread along floors. Vapours may ignite explosively.

Flammability classification (OSHA 29 CFR 1910.106)

- : Flammable liquids - Category 2

Hazardous combustion products

- : Carbon oxides; Aldehydes; Hydrocarbons; irritating fumes and smoke.

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

- : Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire-fighting procedures

- : Fight fires from a safe distance. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- : All persons dealing with the clean-up should wear the appropriate chemically protective equipment. Keep all other personnel upwind and away from the spill/release. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.



ETK Acid Test Kit

ETK (P/N 475360)

SDS Revision Date (mm/dd/yyyy): 09/11/2019

Page 4 of 11

SAFETY DATA SHEET

Environmental precautions : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. For large spills, dike the area to prevent spreading.

Methods and material for containment and cleaning up

: Remove all sources of ignition. Ventilate area of release. Dike for water control. Stop spill or leak at source if safely possible. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Contact the proper local authorities.

Special spill response procedures

: If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802).

US CERCLA Reportable quantity (RQ): Toluene (1000 lbs / 454 kg)

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Wear protective gloves/clothing and eye/face protection. Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Keep away from heat, sparks and open flames. Ground/Bond container and receiving equipment. Use only non-sparking tools. Keep away from acids and incompatibles. Take precautionary measures against static discharges. Always replace cap after use. Keep container tightly closed. Wash thoroughly after handling.

Conditions for safe storage : Store locked up. Store in a cool, dry, well-ventilated area. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.

Incompatible materials : Oxidizing agents

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

| <u>Chemical Name</u> | <u>ACGIH TLV</u> | | <u>OSHA PEL</u> | |
|----------------------|-------------------------------|-------------|------------------------------------|-------------|
| | <u>TWA</u> | <u>STEL</u> | <u>PEL</u> | <u>STEL</u> |
| | Toluene | 20 ppm | N/Av | 200 ppm |
| Ethyl alcohol | N/Av | 1000 ppm | 1000 ppm (1900 mg/m ³) | N/Av |
| potassium hydroxide | 2 mg/m ³ (Ceiling) | N/Av | 2 mg/m ³ (Ceiling) | N/Av |

Exposure controls

Ventilation and engineering measures

: Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Use explosion-proof electrical and ventilating equipment.

Respiratory protection : If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Advice should be sought from respiratory protection specialists. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.

Skin protection : Impervious gloves must be worn when using this product. Advice should be sought from glove suppliers.

Eye / face protection : Wear safety glasses with side shields (or goggles).



ETK Acid Test Kit

ETK (P/N 475360)

SDS Revision Date (mm/dd/yyyy): 09/11/2019

Page 5 of 11

SAFETY DATA SHEET

Other protective equipment : Wear resistant clothing and boots. An eyewash station and safety shower should be made available in the immediate working area.

General hygiene considerations

- : Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Wash hands thoroughly after using this product, and before eating, drinking or smoking.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Clear, red liquid.

Odour : Solvent odor.

Odour threshold : N/Av

pH : N/Av

Melting Point/Freezing point : -30°C (-22°F)

Initial boiling point and boiling range

: 78°C (172°F)

Flash point : 4.4°C (40°F)

Flashpoint (Method) : Seta closed cup

Evaporation rate (BuAe = 1) : > 1

Flammability (solid, gas) : Not applicable.

Lower flammable limit (% by vol.)

: N/Av

Upper flammable limit (% by vol.)

: N/Av

Oxidizing properties : None.

Explosive properties : Not explosive

Vapour pressure : 19 mm Hg

Vapour density : 1.6

Relative density / Specific gravity

: 0.86

Solubility in water : Partially soluble.

Other solubility(ies) : Not available.

Partition coefficient: n-octanol/water or Coefficient of water/oil distribution

: N/Av

Auto-ignition temperature : N/Av

Decomposition temperature : N/Av

Viscosity : < 2 cps

Volatiles (% by weight) : >99%

Volatile organic Compounds (VOC's)

: 860 g/L

Absolute pressure of container

: N/Av

Flame projection length : N/Av

Other physical/chemical comments

: No additional information.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability : Stable under the recommended storage and handling conditions prescribed.



ETK Acid Test Kit

ETK (P/N 475360)

SDS Revision Date (mm/dd/yyyy): 09/11/2019

Page 6 of 11

SAFETY DATA SHEET

Possibility of hazardous reactions

- : No dangerous reaction known under conditions of normal use. Hazardous polymerization does not occur.

Conditions to avoid

- : Avoid heat and open flame. Keep away from direct sunlight. Ensure adequate ventilation, especially in confined areas.

Incompatible materials

- : Oxidizing agents

Hazardous decomposition products

- : None known, refer to hazardous combustion products in Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES

Routes of entry skin & eye : YES

Routes of entry Ingestion : YES

Routes of exposure skin absorption

- : NO

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

- : May cause drowsiness or dizziness. Symptoms may include pain, headache, nausea, vomiting, dizziness, drowsiness and other central nervous system effects.

Sign and symptoms ingestion

- : May cause gastrointestinal irritation. May cause nausea, vomiting, headache and other central nervous system effects. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

Sign and symptoms skin

- : Causes skin irritation. Symptoms may include redness, itching and swelling.

Sign and symptoms eyes

- : Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis.

Potential Chronic Health Effects

- : Prolonged or repeated contact may cause drying, cracking and defatting of the skin.

Mutagenicity

- : Not expected to be mutagenic in humans.

Carcinogenicity

- : No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP. Note that this product contains ethanol, a confirmed animal carcinogen (A3) by the ACGIH and human carcinogen (Group 1) by the IARC; however, this is only applicable when the chemical is present in alcoholic beverages.

Reproductive effects & Teratogenicity

- : This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification: Reproductive toxicity - Category 2 Suspected of damaging fertility or the unborn child.

Sensitization to material

- : Not expected to be a skin or respiratory sensitizer.

Specific target organ effects

- : This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).
Classification:
Specific target organ toxicity, single exposure - Category 3 (narcotic effects)
Specific Target Organ Toxicity, Repeated Exposure - Category 2
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.



ETK Acid Test Kit

ETK (P/N 475360)

SDS Revision Date (mm/dd/yyyy): 09/11/2019

Page 7 of 11

SAFETY DATA SHEET

Medical conditions aggravated by overexposure

: Pre-existing skin, eye, respiratory and central nervous system disorders.

Synergistic materials

: None known or reported by the manufacturer.

Toxicological data

: See below for individual ingredient acute toxicity data.

| <u>Chemical name</u> | <u>LC₅₀(4hr)</u> <u>inh, rat</u> | <u>LD₅₀</u> | |
|----------------------|--|------------------------|-------------------------|
| | | <u>(Oral, rat)</u> | <u>(Rabbit, dermal)</u> |
| Toluene | 7585 ppm (28.1 mg/L) | 5580 mg/kg | 12 125 mg/kg |
| Ethyl alcohol | > 32 380 ppm (61 mg/L) (vapour) | 7060 mg/kg | > 15 800 mg/kg |
| potassium hydroxide | N/Av | 205 mg/kg | > 1260 mg/kg |

Other important toxicological hazards

: None known.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

: Harmful to aquatic life with long lasting effects. Do not allow material to contaminate ground water system. See the following tables for individual ingredient ecotoxicity data.

Ecotoxicity data:

| <u>Ingredients</u> | <u>CAS No</u> | <u>Toxicity to Fish</u> | | |
|---------------------|---------------|-----------------------------|----------------------|-----------------|
| | | <u>LC50 / 96h</u> | <u>NOEC / 21 day</u> | <u>M Factor</u> |
| Toluene | 108-88-3 | 5.4 mg/L (pink salmon) | 1.4 - 4 mg/L | None. |
| Ethyl alcohol | 64-17-5 | > 100 mg/L (Fathead minnow) | N/Av | None. |
| potassium hydroxide | 1310-58-3 | 80 mg/L (Mosquito fish) | N/Av | None. |

| <u>Ingredients</u> | <u>CAS No</u> | <u>Toxicity to Daphnia</u> | | |
|---------------------|---------------|-----------------------------------|----------------------|-----------------|
| | | <u>EC50 / 48h</u> | <u>NOEC / 21 day</u> | <u>M Factor</u> |
| Toluene | 108-88-3 | 3.78 mg/L (Daphnia magna) | 0.53 - 1 mg/L | None. |
| Ethyl alcohol | 64-17-5 | 5012 mg/L (Daphnia magna) | N/Av | None. |
| potassium hydroxide | 1310-58-3 | 56 mg/L Ceriodaphnia (water flea) | N/Av | None. |

| <u>Ingredients</u> | <u>CAS No</u> | <u>Toxicity to Algae</u> | | |
|---------------------|---------------|------------------------------|----------------------------|-----------------|
| | | <u>EC50 / 96h or 72h</u> | <u>NOEC / 96h or 72h</u> | <u>M Factor</u> |
| Toluene | 108-88-3 | N/Av | 10 mg/L/72hr (Green algae) | None. |
| Ethyl alcohol | 64-17-5 | 1000 mg/L/96hr (Green algae) | N/Av | None. |
| potassium hydroxide | 1310-58-3 | N/Av | N/Av | None. |



ETK Acid Test Kit

ETK (P/N 475360)

SDS Revision Date (mm/dd/yyyy): 09/11/2019

Page 8 of 11

SAFETY DATA SHEET

Persistence and degradability

- : No data is available on the product itself.
- Toluene is considered to be readily biodegradable.
- Ethanol is considered to be readily biodegradable.

Bioaccumulation potential

- : No data is available on the product itself. See the following data for ingredient information.

| <u>Components</u> | <u>Partition coefficient n-octanol/water (log Kow)</u> | <u>Bioconcentration factor (BCF)</u> |
|-------------------------------------|--|--------------------------------------|
| Toluene (CAS 108-88-3) | 2.65 | |
| Ethyl alcohol (CAS 64-17-5) | - 0.31 | N/Av |
| potassium hydroxide (CAS 1310-58-3) | N/Ap | N/Ap |

Mobility in soil

- : No data is available on the product itself.

Other Adverse Environmental effects

- : No data is available on the product itself.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal

- : Handle waste according to recommendations in Section 7. Empty containers retain residue (liquid and/or vapour) and can be dangerous.

Methods of Disposal

- : Dispose in accordance with all applicable federal, state, provincial and local regulations.

RCRA

- : If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14. TRANSPORT INFORMATION

| Regulatory Information | UN Number | UN proper shipping name | Transport hazard class(es) | Packing Group | Label |
|---|---|--|----------------------------|---------------|---|
| 49CFR/DOT | UN1993 | Flammable Liquids, n.o.s. (Toluene; Ethanol) | 3 | II |  |
| 49CFR/DOT Additional information | May be shipped as a Limited Quantity according to packaging section 173.150. Refer to 49 CFR Section 173.150. | | | | |
| TDG | UN1993 | FLAMMABLE LIQUID, N.O.S. (Toluene; Ethanol) | 3 | II |  |
| TDG Additional information | Within Canada, the Limited Quantity Exemption may apply for containers which hold specific quantities of the product. Under the TDGR, refer to section 1.17 for Limited Quantity Exemption information, if shipping under this exemption. | | | | |
| ICAO/IATA | UN1993 | Flammable liquid, n.o.s. (Toluene; Ethanol) | 3 | II |  |
| ICAO/IATA Additional information | Refer to ICAO/IATA Packing Instruction | | | | |



ETK Acid Test Kit

ETK (P/N 475360)

SDS Revision Date (mm/dd/yyyy): 09/11/2019

Page 9 of 11

SAFETY DATA SHEET

Special precautions for user : Appropriate advice on safety must accompany the package. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking.

Environmental hazards : This product does not meet the criteria for an environmentally hazardous mixture, according to the IMDG Code. See ECOLOGICAL INFORMATION, Section 12.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
 : Not applicable.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

| <u>Ingredients</u> | CAS # | TSCA Inventory | CERCLA Reportable Quantity(RQ) (40 CFR 117.302): | SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355: | SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical | |
|---------------------|-----------|----------------|--|--|---|--------------------------|
| | | | | | Toxic Chemical | de minimus Concentration |
| Toluene | 108-88-3 | Yes | 1000 lb/ 454 kg | None. | No | 1% |
| Ethyl alcohol | 64-17-5 | Yes | None. | None. | No | N/Ap |
| potassium hydroxide | 1310-58-3 | Yes | 1000 lb/ 454 kg | None. | No | N/Ap |

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Physical hazards (Flammable)Health hazards (Eye irritation; Skin irritation; Reproductive toxicity ;Aspiration hazard; Specific target organ toxicity, repeated exposure ;Specific target organ toxicity, single exposure).

Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds or the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

| <u>Ingredients</u> | CAS # | California Proposition 65 | | State "Right to Know" Lists | | | | | |
|---------------------|-----------|---------------------------|---|-----------------------------|-----|-----|-----|-----|-----|
| | | Listed | Type of Toxicity | CA | MA | MN | NJ | PA | RI |
| Toluene | 108-88-3 | Yes | Developmental | No | No | Yes | No | No | Yes |
| Ethyl alcohol | 64-17-5 | Yes | Cancer (in alcoholic beverages) Developmental (in alcoholic beverages) | Yes | Yes | Yes | Yes | Yes | Yes |
| potassium hydroxide | 1310-58-3 | No | N/Ap | Yes | Yes | Yes | Yes | Yes | Yes |

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.



ETK Acid Test Kit

ETK (P/N 475360)

SDS Revision Date (mm/dd/yyyy): 09/11/2019

Page 10 of 11

SAFETY DATA SHEET

International Information:

Components listed below are present on the following International Inventory list:

| <u>Ingredients</u> | <u>CAS #</u> | <u>European EINECs</u> | <u>Australia AICS</u> | <u>Philippines PICCS</u> | <u>Japan ENCS</u> | <u>Korea KECI/KECL</u> | <u>China IECSC</u> | <u>NewZealand IOC</u> |
|---------------------|--------------|------------------------|-----------------------|--------------------------|-------------------|------------------------|--------------------|-----------------------|
| Toluene | 108-88-3 | 203-625-9 | Present | Present | (3)-2 | KE-33936 | Present | HSR001227 |
| Ethyl alcohol | 64-17-5 | 200-578-6 | Present | Present | (2)-202 | KE-13217 | Present | HSR001144 |
| potassium hydroxide | 1310-58-3 | 215-181-3 | Present | Present | (1)-369 | KE-29139 | Present | HSR001546 |

SECTION 16. OTHER INFORMATION

Legend

- : ACGIH: American Conference of Governmental Industrial Hygienists
CA: California
CAS: Chemical Abstract Services
CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
CFR: Code of Federal Regulations
CNS: Central Nervous System
DOT: Department of Transportation
HMIS: Hazardous Materials Identification System
HSDB: Hazardous Substances Data Bank
IARC: International Agency for Research on Cancer
Inh: Inhalation
LC: Lethal Concentration
LD: Lethal Dose
MA: Massachusetts
MN: Minnesota
MSHA: Mine Safety and Health Administration
N/Ap: Not Applicable
N/Av: Not Available
NFPA: National Fire Protection Association
NJ: New Jersey
NIOSH: National Institute of Occupational Safety and Health
NTP: National Toxicology Program
OSHA: Occupational Safety and Health Administration
PA: Pennsylvania
PEL: Permissible exposure limit
RCRA: Resource Conservation and Recovery Act
RI: Rhode Island
RTECS: Registry of Toxic Effects of Chemical Substances
SARA: Superfund Amendments and Reauthorization Act
STEL: Short Term Exposure Limit
TDG: Canadian Transportation of Dangerous Goods Act & Regulations
TLV: Threshold Limit Values
TWA: Time Weighted Average
WHMIS: Workplace Hazardous Materials Identification System

References

- : 1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2018.
2. International Agency for Research on Cancer Monographs, searched 2019.
3. Canadian Centre for Occupational Health and Safety, CChInfoWeb databases, 2019 (Chempendium, HSDB and RTECS).
4. Safety Data Sheets from manufacturer.
5. US EPA Title III List of Lists - June 2019 version.
6. California Proposition 65 List - June 2019 version.
7. OECD - The Global Portal to Information on Chemical Substances - eChemPortal, 2019.



ETK Acid Test Kit

ETK (P/N 475360)

SDS Revision Date (mm/dd/yyyy): 09/11/2019

Page 11 of 11

SAFETY DATA SHEET

Preparation Date (mm/dd/yyyy)

: 04/20/2015

Reviewed Date SDS (dd/mm/yyyy)

: 11/09/2019

Revision No.

: 2

Revision Information

: All (format change)

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

| | |
|---|---|
| <p>Prepared for: Parker Hannifin Corporation - Sporlan Division 206 Lange Drive, Washington, MO, U.S.A. 63090 Telephone: (636) 239-1111 www.parker.com Direct all enquiries to: Parker Hannifin Corporation - Sporlan Division.</p> |  |
| <p>Prepared by: ICC The Compliance Center Inc. Telephone: (888) 442-9628 (U.S.); (888) 977-4834 (Canada) http://www.thecompliancecenter.com</p> |  |

DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Parker Hannifin Corporation and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Parker Hannifin Corporation expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Parker Hannifin Corporation.

END OF DOCUMENT