

GRAISSE S6959

USAGE

Lubrication and leaktightness of gas valves:

- Gas valves on domestic appliances (cookers, ovens, water heaters, etc.)
- Greasing of cock casings made of metal, glass, etc.

Technical Characteristics

| | |
|---|--|
| Type | Grease containing lithium soap, mineral oil, and molybdenum bisulphate |
| Colour | Black |
| Density | 1.06 |
| Maximum working temperature | 175°C |
| Drop point | 185°C |
| NLGI | 2-3 |
| Suitable for combustible gases, butane, propane, natural gas, etc. | |
| Good level of resistance to temperature and aging | |
| Insoluble in water | |
| High resistance to chemical agents | |
| Outstanding lubricating and anti-sticking power due to high molybdenum bisulphate content | |

Application

For an on/off valve for gas equipment:

Preparation

- Shut the meter down
- Drain the circuit by leaving one burner on.
- Dismantle the valve head and clean it.

Instructions for use

- Apply **GRAISSE S6959** around the plug without leaving any excess.
- Put the head back on and operate the valve several times to spread the grease uniformly.
- Open the meter and check that the valve is not leaking with **DETECTEUR DE FUITE**. (leak detector in aerosol)

For a cooker valve:

Preparation

- Dismantle the button

Instructions for use

- Put the grease between the fixed and moving parts of the valve.
- Do not use too much grease to prevent it from penetrating the valve openings.

Material cleaning

- Solvent grease remover, water-based grease remover
- White Spirit, acetone

Storage

Store at a temperature of between +5°C and +40°C.

At 20°C, the product closed in its original packaging keeps for 5 years.

The safety datasheet is available online at www.quickfds.com. The information contained on the technical datasheet is provided in all good faith and results from measurements made in our laboratory. Given the number of materials, differences in quality and diversity of working methods, we recommend that users perform tests prior to application under actual conditions of use.

This document may be amended in keeping with product development and the state of our knowledge without prior notice and therefore it is recommended to check that you have the latest version before use.



GEB SAS – CS 62062 – Tremblay en France
95972 Roissy Charles de Gaulle Cédex - France
Tel. +33 (0)1 48 17 99 99 - Fax +33 (0)1 48 17 98 00
SIREN no.: 500 674 056

www.geb.fr

p: 2 of 2